



W H COLLIER

Handmade Bricks Since 1863

DECLARATION OF PERFORMANCE

COLCHESTER ORANGE 65MM HANDMADE FACINGS

F603

Declaration includes Special Shapes listed in BS4729 and variants to Category 11 System 4

GROUP HD,CATEGORY II

Facing and rendered masonry, load bearing or non loadbearing masonry structures including internal linings and partitions for building and civil engineering.

System of assessment and verification ----- 4

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Dimensions and Tolerance	215mm X 102.5mm X 65mm Tolerance Class T2 Range Class R1	EN771-1:2011 (+A1:2015)
Configuration	Frogged Unit	
Compressive Strength	Mean 28.7N/mm ²	
Dimensional Stability	NPD	
Bond Strength	Fixed 0.15 N/mm ²	
Active Soluble Salts	S2	
Reaction to Fire	Class A1	Commission Decision 2000/605/EC
Water Absorption	17%	EN771-1:2011 (+A1:2015)
Water Vapour Permeability	50/100	
Direct Airborne Sound Insulation	NPD	
Thermal properties	NPD	
Freeze Thaw	F2	
Dangerous Substances	NPD	

The performance of the product identified above is in conformity with the declared values

Signed on behalf of W H COLLIER LTD

N Lax

Name: Nikki Lax

Position: Managing Director

Date 25/05/2022



W H Collier Limited, Church Lane, Marks
Tey, Colchester. Essex. CO6 1LN

BS EN 771-1:2011 (+A1:2015)

COLCHESTER ORANGE 65mm HANDMADE FACINGS

F604

Declaration includes Special Shapes listed in BS4729 and variants to Category 11 System 4
GROUP HD, CATEGORY II, 215 x 102.5 x 65mm Clay masonry unit

**Dimensions and
Tolerance:**

Tolerance Category: T2

Range Category: R1

Compressive strength: 25N/mm² (⊥ bed face)

Water Absorption: 17%

**Durability against freeze-
thaw:** F2

**Active Soluble Salt
Content:** S2

Reaction to Fire: Class A1

**Bond Strength (fixed value
from EN 998-2):** Fixed 0.15 N/mm²

**Water Vapour Diffusion
Coefficient (EN 175 table
value):** 50/100

**Direct Airborne Sound
Insulation:** NPD

**Equivalent Thermal
Conductivity:** NPD

Dimensional Stability: NPD

Dangerous Substances: NPD

Dry Weight Per Brick: 2.1Kg

Bricks Per Pack 400

Note: Information on dangerous substances will only be given when and where required in the appropriate form. See annex ZA.3 of BS EN 771-1:2011